

# DEWALT®

**OSHA COMPLIANT**  
1926.1153

# DUST SOLUTIONS



# ARE YOU COMPLIANT?

The Occupational Safety and Health Administration (OSHA) rules with the intent to limit workers' exposure to respirable crystalline silica.



Compliant Versions  
available by Sept 2017



## TOOLS

Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.

- Read operator's manual provided with tool and accessories.
- To minimize dust emissions use recommended shroud or cowl and dust extractor

## ACCESSORIES AND SHROUDS

Use drill or grinder equipped with commercially available shroud or cowl with dust collection system.

- All DEWALT shrouds and dust collection systems are commercially available.

## DUST EXTRACTORS

Dust collector must provide the air flow recommended by the tool manufacturer, or greater, and have a filter with 99% or greater efficiency. Dust collector must have a cyclonic pre-separator or filter-cleaning mechanism. Cleaning/Drilling holes requires a vacuum with a HEPA filter.

- Both DWV010 and DWV012 provide the necessary airflow for drilling and hammering applications.
- Both DWV010 and DWV012 ship with dual HEPA filters, which have an efficiency of 99.97% of all particles greater than or equal to 0.3 microns.
- Both DWV010 and DWV012 have a timed automatic filter-cleaning mechanism.
- Surfacing, Tuckpointing, and Cutting with grinder requires 25 CFM per inch of wheel diameter, a filter cleaning mechanism, and 99% or greater efficiency.

**PERFORM  
PROTECT**

**YOUR FIRST LINE OF DEFENSE.™**

## OSHA COMPLIANT 1926.1153 DRILLING

	TOOL	ATTACHMENT   ADAPTOR	EXTRACTOR
SDS+ DRILLING	<b>SDS PLUS</b> $\leq 1-1/8"$		
	<b>CORDLESS OPTIONS</b>		
	 DCH273 DCH293	 DWH303DH DWH304DH	
	 D25052 D25133 D25260 D25213 D25223 D25262 D25263 D25313 D25323 D25324 D25333 DC212 DCH133 DCH213 DCH253	 D25301D Dust Extractor Telescope with Hose or DWV9130 AirLock™ Adaptor Included on D25301D	 DWV012 or DWV010 Dust Extractor + DWV9000 AirLock™ Adaptor Included on DWV012 & DWV010
	$1-1/8"$	 DWH050K Large Hammer Drilling Dust Extraction	 DWV012 or DWV010 Dust Extractor + DWV9000 AirLock™ Adaptor Included on DWV012 & DWV010
SDS MAX & SPLINE DRILLING	<b>SDS MAX</b>		
	 DCH481 D25481 D25501 D25601 D25603 D25721 D25723 D25761 D25763	 DWH050K Large Hammer Drilling Dust Extraction or DWH053K Large Hammer Chipping Dust Extraction	 DWV012 or DWV010 Dust Extractor
	<b>SPLINE</b>		
	 D25553 D25651	 DWA58058 SDS MAX Hollow Bit	 DWV010 Dust Extractor
CHIPPING & DEMOLITION	<b>SDS MAX</b> <b>SPLINE</b>		
	<b>HEX 3/4"</b>		
	 D25810 D25831 D25851 D25891 D25899 D25901 D25941	 DWH053K Large Hammer Chipping Dust Extraction	 DWV010 Dust Extractor + DWV9000 AirLock™ Adaptor Included on DWV012 & DWV010
	<b>HEX 1-1/8"</b>		
	 D25960 D25980	 DWH052K Breaker Dust Extraction	 DWV010 Dust Extractor + DWV9000 AirLock™ Adaptor Included on DWV012 & DWV010

## OSHA COMPLIANT 1926.1153 GRINDING<sup>1</sup>

	TOOL	ATTACHMENT   ADAPTOR	EXTRACTOR
5-6" TUCKPOINTING / CUTTING*	 DWE402 DWE402N		 DWV012 or DWV010 Dust Extractor + DWV9000 AirLock™ Adaptor Included on DWV012 & DWV010
	 DWE4214 DWE4222N		
	 DWE43114 DWE43114N DWE43144 DWE43144N DWE43131 DWE43140 DWE43115 DWE43115N DWE43113 DWE43116 DWE43066 DWE43066N	 DWE46100 5 5/6" Cutting and Tuckpointing Dust Shroud	
5" SURFACING	 DWE402 DWE402N DWE4214 DWE4222N DWE43114 DWE43114N DWE43144 DWE43144N DWE43131 DWE43140 DWE43115 DWE43115N DWE43113 DWE43116 DWE43066 DWE43066N	 DWE46152 5" Surface Grinding Dust Shroud	 DWV012 or DWV010 Dust Extractor + DWV9000 AirLock™ Adaptor Included on DWV012 & DWV010

DeWALT's Perform & Protect™ line of Power Tools is designed to provide a high level of one or more of the following: control, dust containment, or low vibration, without sacrificing performance.

Copyright ©2017 DeWALT. The following are trademarks for one or more DeWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

1. System is compliant to the Exposure Control Methods described in Table 1 of 29 CFR 1926.1153 when outlined components are operated and maintained in accordance to manufacturer's instructions, assuming that airflow is measured in accordance with the motor/fan system test. See 'Appendix' for full system and compliance details. OSHA is reviewing the exact requirements for dust extraction in these applications.

\* Also fits previous DeWALT models D28402, D28402N, D28110, D28112, D28114, D28114N, D28144, D28144N, D28131, D28140, D28115, D28115N, D28116, D28065, D28065N, D28066N