

DEWALT®

FLEXVOLT™

POWER OF CORDED. | FREEDOM OF CORDLESS.



20V^{MAX}
LITHIUM ION



60V^{MAX}
LITHIUM ION



120V^{MAX}
LITHIUM ION
(2 x 60V MAX*)



2016 CORDLESS POWER TOOL
AND ACCESSORY CATALOG

FLEXVOLT™

WORLD'S FIRST

BATTERY PACK THAT
AUTOMATICALLY CHANGES
VOLTAGE WHEN YOU
CHANGE TOOLS.



POWER OF CORDED.
FREEDOM OF CORDLESS.

COMPATIBLE

BATTERY WORKS WITH
OUR FASTEST GROWING
CORDLESS SYSTEM.

20V^{MAX*}
LITHIUM ION



UP TO
4X RUNTIME**

EXPANDABLE

LINE OF DEDICATED,
POWERFUL, 60V MAX*
BRUSHLESS TOOLS.

60V^{MAX*}
LITHIUM ION

MORE THAN
3X BATTERY
POWER†



POWERFUL

LINE OF 12" 120V MAX*
BRUSHLESS TOOLS.

120V^{MAX*}
LITHIUM ION

(2 x 60V MAX*)

**the POWER
of CORDED**



* Maximum initial battery voltage (measured without a workload) is 4, 20, 60 and 120 volts. Nominal voltage is 3.6, 18, 54 and 108. 120V MAX* is based on using 2 DeWALT 60V MAX* lithium-ion batteries combined.

** With FLEXVOLT™ 60V MAX* battery when used with DeWALT 20V MAX* tools

† Vs. DeWALT 18V NiCad battery


PROPRIETARY BATTERY TECHNOLOGY

WORLD'S FIRST
BATTERY PACK THAT AUTOMATICALLY CHANGES
VOLTAGE WHEN YOU CHANGE TOOLS.



PARALLEL MODE =
RUNTIME

IN 20V MAX* TOOLS THE
BATTERY DELIVERS UP TO
4 TIMES THE RUNTIME**.



SERIES MODE =
POWER

IN 60V MAX* TOOLS THE
BATTERY DELIVERS THE
POWER OF A CORDED TOOL.



ONE BATTERY, TWO VOLTAGES.

FLEXVOLT™

POWER OF CORDED. | FREEDOM OF CORDLESS.

60v MAX^{*}
LITHIUM ION

the POWER
of CORDED

CUTS 302
UP TO
LINEAR FEET PER CHARGE**

8-1/4" BLADE

24" FENCE TO BLADE

60v BRUSHLESS MOTOR

INTRODUCING OUR FIRST
8-1/4" BLADE CORDLESS TABLE SAW.

FLEXVOLT™ tools deliver corded tool performance with the freedom of a cordless tool.

60V MAX* performance whenever you need it, wherever you want it. Built Guaranteed Tough®, by DeWALT.

DEWALT

GUARANTEED TOUGH.

DCS7485 8-1/4" Table Saw with 24" Rip Capacity



60V MAX*
LITHIUM ION
the POWER
of CORDED

UP TO
302 LINEAR
FEET
3/4" OSB using DCB606 battery and
FLEXVOLT™ 8-1/4" blade

- Cordless convenience with the power of a corded tool
- Rack and pinion fence system
- On board storage for components included with saw


DCS575 7-1/4" Circular Saw with Brake



60V MAX*
LITHIUM ION
the POWER
of CORDED
MORE THAN
3X POWER
vs 18V™

UP TO
339 Cuts
2x4 SPF Lumber using DCB606
battery

- Cordless convenience with the power of a corded tool
- 7-1/4" full size blade for corded capacity
- Electronic brake stops the blade after the trigger is released



**vs. DC390 using 18V NiCad battery

SPECIFICATIONS	
No Load Speed	5800 rpm
Blade Diameter	8-1/4"
Arbor Size	5/8"
Depth of cut at 45°	1-3/4"
Depth of cut at 90°	2-1/2"
Max rip to right of blade	24"
Max rip to left of blade	12-1/2"
Tool Weight	46.9 lbs.

CONFIGURATIONS	
DCS7485T1	INCLUDES: DCS7485 Table Saw, (1) DCB606 60V MAX* FLEXVOLT™ 6.0Ah Battery, Fast Charger, Blade, (2) Blade Wrenches, and Push Stick
DCS7485B	INCLUDES: DCS7485 Table Saw, Blade, (2) Blade Wrenches, and Push Stick



SPECIFICATIONS	
MWO	1500
No Load Speed	5800 rpm
Blade Diameter	7-1/4"
Bevel Capacity	0-57°
Arbor Size	5/8"
Depth of cut at 45°	1-7/8"
Depth of cut at 90°	2-9/16"
Shoe	Aluminum
Tool Weight	8.2 lbs.

CONFIGURATIONS	
DCS575T2	INCLUDES: DCS575 7-1/4" Circular Saw, (2) DCB606 60V MAX* FLEXVOLT™ 6.0Ah Batteries, Fast Charger, Blade, Blade Change Wrench, and Kit Bag
DCS575T1	INCLUDES: DCS575 7-1/4" Circular Saw, (1) DCB606 60V MAX* FLEXVOLT™ 6.0Ah Battery, Fast Charger, Blade, Blade Change Wrench, and Kit Bag
DCS575B	INCLUDES: DCS575 7-1/4" Circular Saw, Blade, and Blade Change Wrench



DCS388 Reciprocating Saw



60V^{MAX}
LITHIUM ION

the POWER
of CORDED

MORE THAN
3X POWER
vs 18V^{**}

UP TO
158 Cuts
2x4 SPF Lumber using DCB606 battery

- Keyless lever-action blade clamp allows for quick and easy blade changes
- 1-1/8" Stroke length delivers a fast cutting speed
- Variable speed trigger with 0-3000 spm provides increased blade control and fast cut speeds

DCG414 4-1/2" - 6" Grinder with Kickback Brake



PERFORM PROTECT

DeWALT's Perform & Protect® line of Power Tools is designed to provide a high level of safety or some of the following features, with confidence, or their absence, without compromising performance.

60V^{MAX}
LITHIUM ION

the POWER
of CORDED

MORE THAN
3X POWER
vs 18V^{**}

UP TO
126 Cuts
1/2" Rebar using DCB606 battery and 6" FLEXVOLT cutting wheel

- 13 Amp Equivalent power†
- Kick Back Break engages when a pinch, stall, or bind-up event is sensed and the electronic brake engages with maximum force to quickly stop the wheel, reduce the movement of the grinder, and shut the grinder off
- The same tool cuts and grinds with wheels from 4-1/2" - 6" with additional guard

† as compared to D28144
Optional cutting guard and cutting wheel shown in photo to the left



RECIPROCATING SAW TYPE	CATALOG #	STROKES PER MINUTE	CUTS AS FAST AS	CUTS PER CHARGE
CORDED	DWE304	0-2800 SPM	3.23 SECONDS In 2x4 SPF Lumber	UP TO 112 Using a DCS205 Battery
CORDLESS	DCS380P2	0-3000 SPM	2.53 SECONDS In 2x4 SPF Lumber using a DCB205 battery	UP TO 158 Using a FLEXVOLT™ 6.0 Ah Battery
FLEXVOLT	DCS388P2	0-3000 SPM	2.32 SECONDS In 2x4 SPF Lumber using a FLEXVOLT™ 6.0 Ah battery	

**vs. DC385 using 18V NiCad battery

SPECIFICATIONS	
Keyless Blade Clamp	Yes
Stroke/Min	0-3000 spm
Stroke Length	1-1/8"
Electric Brake	Yes
Tool Weight	7.8 lbs.

CONFIGURATIONS	
DCS388T2	INCLUDES: DCS388 Reciprocating Saw, (2) DCB606 60V MAX* FLEXVOLT™ 6.0Ah Batteries, Blade, Fast Charger, and Kit Bag
DCS388T1	INCLUDES: DCS388 Reciprocating Saw, (1) DCB606 60V MAX* FLEXVOLT™ 6.0Ah Battery, Blade, Fast Charger, and Kit Bag
DCS388B	INCLUDES: DCS388 Reciprocating Saw and Blade



GRINDER TYPE	CATALOG #	CAPACITY	CUTS AS FAST AS	CUTS PER CHARGE
CORDED	DWE4011	4-1/2"	4.49 SECONDS In 1/2" rebar using a 4.5" FLEXVOLT™ cutting wheel	UP TO 80 Using a DCS205 battery and 4.5" rebar wheel
CORDLESS	DCG412P2	4-1/2"	5.10 SECONDS In 1/2" rebar using DCS205 and 4.5" FLEXVOLT™ cutting wheel	UP TO 126 Using a FLEXVOLT™ 6.0 Ah battery and 6" FLEXVOLT™
FLEXVOLT	DCG414	4-1/2"-6"	2.66 SECONDS In 1/2" rebar using a FLEXVOLT™ 6.0 Ah battery and 6" FLEXVOLT™ cutting wheel	

**vs. DC411 using 18V NiCad battery

SPECIFICATIONS	
MWO	1700 W
Max Horsepower	2.2 HP
No Load Speed	9000 rpm
Spindle Lock	Yes
Spindle Thread	5/8" -11
Tool Weight	4.66 lbs.

CONFIGURATIONS	
DCG414T2	INCLUDES: DCG414 Grinder, (2) DCB606 60V MAX* FLEXVOLT™ 6.0Ah Batteries, Fast Charger, Side Handle, 4-1/2" Type 27 Wheel, 4-1/2" Type 27 Guard, 6" Type 27 Guard, Wrench, Flanges, and Kit Bag
DCG414T1	INCLUDES: DCG414 Grinder, (1) DCB606 60V MAX* FLEXVOLT™ 6.0Ah Battery, Fast Charger, Side Handle, 4-1/2" Type 27 Wheel, 4-1/2" Type 27 Guard, 6" Type 27 Guard, Wrench, Flanges, and Kit Bag
DCG414B	INCLUDES: DCG414 Grinder, Side Handle, 4-1/2" Type 27 Wheel, 4-1/2" Type 27 Guard, 6" Type 27 Guard, Wrench, and Flanges



DCD460 1/2" VSR Stud and Joist Drill with E-CLUTCH® System

60V^{MAX}
LITHIUM ION
the POWER of CORDED

UP TO
138 Holes
2-9/16" in 2x10 SPF using DCB606 battery

- Cordless convenience with the power of a corded tool
- E-CLUTCH® System and Mechanical clutch help keep user in control and protect the tool
- 2-Speed Transmission and VSR Tigger allows user to dial in appropriate speed for application

STUD AND JOIST DRILL TYPE CATALOG # NO LOAD SPEED CUTS AS FAST AS

CORDED



DWD460

0-330/ 0-1300 RPM

3.22 SECONDS
In 2-9/16" self feed in single 2x10 SPF

HOLES PER CHARGE
2X10 SPF

UP TO
138
Using a FLEXVOLT™ 6.0 Ah Battery

FLEXVOLT

60V^{MAX}
LITHIUM ION

DCD460

0-300/ 0-1250 RPM

2.64 SECONDS
In 2-9/16" self feed in single 2x10 SPF using a FLEXVOLT™ 6.0 Ah battery

SPECIFICATIONS

Chuck Size	1/2"
No Load Speed	0-300/0-1250 rpm
Gear Reduction	Triple
E-CLUTCH® System	Yes
Tool Weight	10.6 lbs.

CONFIGURATIONS

DCD460T2	INCLUDES: DCD460 Drill, (2) DCB606 60V MAX* FLEXVOLT™ 6.0Ah Batteries, Fast Charger, Chuck Key and Holder, 2-Position Side Handle, Adjustable Bail Handle and Kit Bag
DCD460T1	INCLUDES: DCD460 Drill, (1) DCB606 60V MAX* FLEXVOLT™ 6.0Ah Battery, Fast Charger, Chuck Key and Holder, 2-Position Side Handle, Adjustable Bail Handle and Kit Bag
DCD460B	INCLUDES: DCD460 Drill, Chuck Key and Holder, 2-Position Side Handle and Adjustable Bail Handle



BUILD ANYTHING. ANYWHERE.™

FLEXVOLT™ tools combine the power and utility of a full sized corded tool with the go anywhere freedom of a cordless tool. Runtime when you want it, power when you need it. Built Guaranteed Tough®, by DeWALT®.

60V^{MAX}
LITHIUM ION

MORE THAN
3X POWER**

NO EXTENSION CORDS.
NO POWER OUTLETS.
NO EXCUSES.

DeWALT

FLEXVOLT

POWER OF CORDED. | FREEDOM OF CORDLESS.

**vs. DC390 using 18V NiCad battery

FLEXVOLT.com | 12

OUR
FASTEST GROWING
SYSTEM

FLEXVOLT™ = COMPATIBILITY



20V^{MAX*}
LITHIUM ION

UP TO
4X^{runtime}

FLEXVOLT™
6.0 Ah BATTERY

4X^{battery capacity}

COMPATIBLE BATTERIES

FLEXVOLT™ BATTERIES WORK WITH EXISTING 20V MAX* TOOLS.

COMPATIBLE CHARGERS

FLEXVOLT™ BATTERIES WORK WITH EXISTING 20V MAX* CHARGERS.

BATTERIES THAT ADD RUNTIME

FLEXVOLT™ BATTERIES ADD UP TO 4X RUNTIME.**

ONE POWERFUL SYSTEM

FLEXVOLT™ TOOLS PUT CORDED POWER IN YOUR TOOLBOX WITHOUT THE HASSLE OF CORDED TOOLS.

60V^{MAX*}
POWER OF CORDED



20V^{MAX*}
COMPATIBLE



DCK299D1T1



2 x 60V MAX* =
120V^{MAX*}

OUR
MOST ADVANCED
SYSTEM

**With FLEXVOLT™ 60V MAX* battery when used with DeWALT 20V MAX* tools
† vs. DeWALT 20V MAX* 1.5Ah battery



DCL070 Corded/Cordless Bluetooth® LED Large Area Light with Built-In Battery Charger

DCB1800 1800 Watt Portable Power Station™



With DeWALT Tool Connect App:
CONNECT. CONTROL. ALERT.™



UP TO 7000 LUMENS

- AC/DC light with dimming setting ranging from 500 – 7000 lumens
- Scheduler for easy programming
- Charger alert notifies users through Tool Connect™ App of battery status
- Stackable for easy transport of multiple units to a jobsite



4 20V BATTERIES IN

15 AMPS OUT

3600 Peak Output from 4 20V MAX* batteries

- 1800 watts (15 amp) continuous
- No gas needed to run, no engine emissions, and low noise
- Multiport parallel charger when plugged into outlet
- Portable power when you need it on the jobsite and beyond

SPECIFICATIONS	
AC Lumens	7000 MAX
DC Lumens in ECO mode	3500 MAX
Dimmer	Yes
Bulb	LED
Tool Weight	27 lbs.

CONFIGURATIONS	
DCL070T1	INCLUDES: DCL070 LED Area Light, (1) DCB606 60V MAX* FLEXVOLT™ 6.0Ah Battery, Fast Charger
DCL070	INCLUDES: DCL070 LED Area Light



CONFIGURATIONS	
DCB1800M3T1	INCLUDES: DCB1800 Portable Power Station™, (3) 20V MAX* XR® 4.0Ah Batteries, (1) DCB606 60V MAX* FLEXVOLT™ 6.0Ah Battery
DCB1800B	INCLUDES: DCB1800 Portable Power Station



The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by DeWALT is under license. Other trademarks and trade names are those of their respective owners

DCR025 Jobsite Bluetooth® Radio Charger



2 AC outlets, 10 amp max



Charges 12V MAX*, 20V MAX* and FLEXVOLT™ batteries



Oversize storage box contains 2.1 amp USB charging and Aux port

SPECIFICATIONS	
Accepts Batteries	12V MAX*/20V MAX*/FLEXVOLT™
Charge Rate	3 Amps
USB Charge Rate	2.1 Amps
Speaker Wattage	20 Amps per channel
Tool Weight	14.4 lbs.

CONFIGURATIONS	
DCR025	INCLUDES: DCR025 Wireless Jobsite Bluetooth® Radio Charger



The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by DeWALT is under license. Other trademarks and trade names are those of their respective owners

DCK299D1T1 Hammerdrill / Impact Driver Combo Kit



20V MAX*
LITHIUM ION
UP TO
4X RUNTIME**

UP TO
159 Holes
Using 2-9/16" self feed
bit in 2x10 SPF using DCB606 battery

- Patented 3-Speed Transmission
- 60 Lumens LED with 20-Min Spotlight Mode
- Carburized Metal Ratcheting Chuck
- 820 UWO of Extreme Power

DCD996 SPECIFICATIONS	
Max Power	820 UWO
Max RPM	0-450/0-1300/0-2000
Clutch Settings	11
Tool Weight	3.4 lbs.

DCF887 SPECIFICATIONS	
Anvil Type	1/4" Hex
No Load Speed	0-1000/0-2800/0-3250 rpm
Impacts/Min	0-3600 ipm
Max Torque	0-240/1500/1825 in.-lbs.
Tool Weight	2.1 lbs.

DCK299D1T1	
Includes	DCD996 1/2" 3-Speed Brushless Hammerdrill, DCF887 1/4" 3-Speed Brushless Impact Driver, (1) DCB606 60V MAX* FLEXVOLT™ 6.0Ah Battery, (1) DCB203 (2.0 Ah) 20V MAX* Lithium Ion Battery Pack, Charger, (2) Belt Hooks, Contractor Bag, 360° Side Handle



**With FLEXVOLT™ 60V MAX* battery when used with DeWALT 20V MAX* tools

FLEXVOLT™

POWER OF CORDED. | FREEDOM OF CORDLESS.

120v MAX*
LITHIUM ION

OR

**120V CORDED
ADAPTER**



**the POWER
of CORDED**

2X 60v MAX*
EQUALS 120v MAX*

120v AC/DC
BRUSHLESS MOTOR

**SLIDING
COMPOUND MITER**

12"
BLADE

INTRODUCING OUR FIRST **12" BLADE CORDLESS MITER SAWS.**

FLEXVOLT™ tools deliver corded tool performance with the freedom of a cordless tool.

120V MAX* performance whenever you need it, wherever you want it.

Built Guaranteed Tough®, by DEWALT.

DEWALT®

GUARANTEED TOUGH.

Cordless/Cordless Miter Saws



UP TO
289 Cuts
3-1/4" Base Molding using DCB606 battery

- Integrated adjustment-free Cutline™ Blade Positioning System for accuracy and visibility
- High visibility bevel scale makes bevel angle adjustments accurate and easy
- Brushless motors provide long runtime compared to brushed motors




120v MAX*
LITHIUM ION

CORDED OR CORDLESS



DHS790 12" DOUBLE BEVEL SLIDING MITER SAW WITH CUTLINE™ SYSTEM




SPECIFICATIONS	
No Load Speed	3800 rpm
Blade Diameter	12"
Bevel Capacity	0-49°
Arbor Size	5/8" or 1"
Tool Weight	56 lbs.

CONFIGURATIONS	
DHS790AT2	INCLUDES: DHS790 Miter Saw, (2) DCB606 60V MAX* FLEXVOLT™ Lithium Ion Batteries, Dual Charger, DCA120 Corded Power Supply, Blade, Blade Wrench, and Dust Bag
DHS790T2	INCLUDES: DHS790 Miter Saw, (2) DCB606 60V MAX* FLEXVOLT™ Lithium Ion Batteries, Dual Charger, Blade, Blade Wrench, and Dust Bag
DHS790AB	INCLUDES: DHS790 Miter Saw, DCA120 Corded Power Supply, Blade, Blade Wrench, and Dust Bag



DHS716 12" DOUBLE BEVEL MITER SAW WITH CUTLINE™ SYSTEM



SPECIFICATIONS	
No Load Speed	3800 rpm
Blade Diameter	12"
Bevel Capacity	0-48°
Arbor Size	5/8" or 1"
Tool Weight	44 lbs.

CONFIGURATIONS	
DHS716AT2	INCLUDES: DHS716 Miter Saw, (2) 60V MAX* FLEXVOLT™ Lithium Ion Batteries, Dual Charger, DCA120 Power Supply, Blade, Blade Wrench, and Dust Bag
DHS716T2	INCLUDES: DHS716 Miter Saw, (2) 60V MAX* FLEXVOLT™ Lithium Ion Batteries, Dual Charger, Blade, Blade Wrench, and Dust Bag
DHS716AB	INCLUDES: DHS716 Miter Saw, DCA120 Power Supply, Blade, Blade Wrench, and Dust Bag



Batteries and Chargers



DCB606 SPECIFICATIONS	
Voltage	20V/60V MAX*
Capacity in 60V Tool	2.0Ah
Capacity in 20V Tool	6.0Ah
Charge Time (Fast Charger)	60 Mins
Cell Chemistry	Li-ion
Fuel Guage	Yes
Weight	2.3 lbs.

FLEXVOLT™ 6.0 Ah battery provides

4X BATTERY CAPACITY

vs. DeWALT 20V MAX* 1.5Ah battery

- One battery supports three different tool platforms
- Proprietary terminal design: connect in parallel for 20V MAX* or connect in series for 60V MAX*



DCB118 SPECIFICATIONS	
Supported Voltage	20V/60V MAX*
Fan Cooling	Yes
Charge Time	60 Mins
Battery Chemistry	Li-ion
Wall Mountable	Yes
Hot/Cold Pack Detection	Yes
Weight	1.5 lbs.

FLEXVOLT

HIGH EFFICIENCY ACCESSORIES™



ENGINEERED TO MAXIMIZE RUNTIME.



Submicron Grade Carbide Tips
for long life




Thin Kerf Design
for smooth, efficient cuts



High Performance Ceramic Grain
stays sharp for fast, efficient cuts



High Density Grain Concentration
for fast cutting and low heat build-up





Patented Body Slots



Also Available:

8-1/4"

12"



Also Available:

Flap Discs

Grinding Wheels






Self-Feed Pilot Bit
for fast, efficient cutting




Carbide Teeth
for long life



Thin Kerf Design
for high efficiency



14/18 Tooth Pattern
for fast cuts



TOUGH COAT® Finish
helps to reduce heat build up for efficient cuts




High Speed Steel Teeth
for long life and durability



Wood Reciprocating Saw Blades


Also Available:

Hole Saw Life:
Average Number of Holes



Average number of holes in Pine 2 x 10 with 10' hole.

Reciprocating Blade Life:
Average Number of Cuts



Average number of cuts in 5/8" rebar



CIRCULAR SAW BLADES					
SKU	Diameter	Tooth Count	Arbor	Max RPM	Pack
DWAFV3724	7 1/4"	24	5/8"	7,000	1
DWAFV3736	7 1/4"	36	5/8"	7,000	1
DWAFV3760	7 1/4"	60	5/8"	7,000	1
DWAFV37243	7 1/4"	24	5/8"	7,000	1
DWAFV3836	8 1/4"	36	5/8"	7,000	1
DWAFV3824	8 1/4"	24	5/8"	7,000	1
DWAFV31278	12"	78	1"	4,800	1
DWAFV31260	12"	60	1"	4,800	1

CUTTING WHEELS						
SKU	Diameter	Thickness	Arbor	Type	Max RPM	Pack
DWAFV84518	4-1/2"	1/8"	7/8"	27	13300	25
DWAFV84518H	4-1/2"	1/8"	5/8"-11	27	13300	10
DWAFV86045	6"	0.045"	7/8"	1	10100	25
DWAFV845045	4-1/2"	0.045"	7/8"	1	13300	25

FLAP DISCS						
SKU	Diameter	Grit	Arbor	Type	Max RPM	Pack
DWAFV84540	4-1/2"	40	7/8"	29	13300	10
DWAFV84560	4-1/2"	60	7/8"	29	13300	10
DWAFV84580	4-1/2"	80	7/8"	29	13300	10
DWAFV84540H	4-1/2"	40	5/8"-11	29	13300	5
DWAFV84560H	4-1/2"	60	5/8"-11	29	13300	5
DWAFV84580H	4-1/2"	80	5/8"-11	29	13300	5

GRINDING WHEELS						
SKU	Diameter	Thickness	Arbor	Type	Max RPM	Pack
DWAFV84514	4-1/2"	1/4"	7/8"	27	13300	25
DWAFV84514H	4-1/2"	1/4"	5/8"-11	27	13300	10

HOLE SAWS		
SKU	Diameter	Pack
DWAFV0138	1 3/8"	1
DWAFV0218	2 1/8"	1
DWAFV0214	2 1/4"	1
DWAFV02916	2 9/16"	1
DWAFV02916PB	2 9/16"	1 w/ Pilot Bit
DWAFV03	3"	1
DWAFV0338	3 3/8"	1
DWAFV0358	3 5/8"	1
DWAFV0400	4"	1
DWAFV0414	4 1/4"	1
DWAFV04516	4 5/16"	1
DWAFV0458	4 5/8"	1
DWAFV0514	5 1/4"	1
DWAFV0614	6 1/4"	1
DWAFV0PB	Pilot Bit	1
DWAFV0PBM	Mandrel, Pilot Bit	1
DWAFV07SET	7 PC. Set	1

RECIPROCATING SAW BLADES			
SKU	Blade Length	TPI	Pack
DWAFV413SET	Multiple	Multiple	1
DWAFV48SET	Multiple	Multiple	1
DWAFV481418	8"	14/18 TPI	5
DWAFV461418	6"	14/18 TPI	5
DWAFV466	6"	4/6 TPI	5
DWAFV496	9"	4/6 TPI	5

FLEXVOLT™

COMING SOON



60v

MAX

LITHIUM ION

1-9/16" Rotary Hammer Kit with E-CLUTCH® System (Includes FLEXVOLT™ 9.0 Ah Battery)

MODEL DCH481X2



20v

MAX

LITHIUM ION

60v

MAX

LITHIUM ION

FLEXVOLT™ 9.0 Ah Battery

MODEL DCB609



60v

MAX

LITHIUM ION

Blower Kit (Includes FLEXVOLT™ 9.0 Ah Battery)

MODEL DCBL770X1



60v

MAX

LITHIUM ION

Plunge Saw Kit (Includes FLEXVOLT™ 6.0 Ah Battery)

MODEL DCS520T1



60v

MAX

LITHIUM ION

16" Chainsaw Kit (Includes FLEXVOLT™ 9.0 Ah Battery)

MODEL DCCS670X1



60v

MAX

LITHIUM ION

15" String Trimmer Kit (Includes FLEXVOLT™ 9.0 Ah Battery)

MODEL DCST970X1

DEWALT®

FLEXVOLT™



POWER OF CORDED. | FREEDOM OF CORDLESS.™

Dealer Stamp

TOOL WARRANTY

3 YEAR	1 YEAR	90 DAY
LIMITED WARRANTY	FREE SERVICE	MONEY BACK GUARANTEE

BATTERY WARRANTY

3 YEAR	3 YEAR
LIMITED WARRANTY	FREE SERVICE

Copyright ©2016 DEWALT. The following are examples of trademarks for one or more DEWALT power tools and accessories: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.
DWFVCAT16

1-800-4 DEWALT®

www.FLEXVOLT.com