

DEWALT®



 MECHANICAL

 PLUMBING



INNOVATION FOR THE **TRADES**™

DEWALT

DCE400 20V MAX* 1" PEX EXPANDER



AUTOMATIC ROTATING HEAD
For even expansion

PEX EXPANDER HEADS
Expands 3/8" - 1"
Type-A PEX pipe

FULLY ACTUATED TRIGGER
For easy and convenient
activation in tight spaces

DUAL SIDED HANG HOOK
Can be mounted on either
side of the tool

RUBBER OVERMOLD
Comfortable ergonomic grip

BRIGHT LED LIGHT
Helps to illuminate work area

DUAL SIDED BELT HOOK
Can be mounted on either
side of the tool



SPECIFICATIONS

Material	Type-A PEX Tubing Only
Expansion Range	3/8" - 1"
Speed	60 SPM
Stroke Length	14.9 mm
Tool Length	6.75"
Tool Weight (tool only)	3.93 lbs

AVAILABLE OPTIONS



DCE400B
DCE400 PEX Expander, (3) Expander Heads (1/2", 3/4", 1"), belt hook, PEX Expander Grease and Kit Box.



DCE400D2
DCE400 PEX Expander, (2) DCB203 XR[®] Lithium Ion Batteries (2.0 Ah), (3) Expander Heads (1/2", 3/4", 1"), PEX Expander Grease, Belt Hook, Charger and Kit Box.

PEX TOOL EXPANSION HEADS

(sold separately)



GREASE TUBE
(sold separately)



DCE400GR

FASTEST PEX EXPANDER ON THE MARKET**

**Compared to competitive PEX Expander average application speed using 1/2", 3/4", and 1" Pex-A pipe

DCD200 20V MAX* XR® BRUSHLESS DRAIN SNAKE



EASY TO REMOVE DRUM
Easily and quickly change out cable

BLACK OXIDE COATED CABLE WITH HIGH PERFORMANCE INNER CORE
Helps to prevent cable from rusting

EASY RELEASE
Pull in to lock, out to unlock

FIXED SHROUD
Comfortably rest unit without it spinning

CONVENIENCE OF CORDLESS
Saves time on the job site not having to deal with cords

VARIABLE SPEED TRIGGER
Easy to control speed

PIVOTING 3-MODE LED LIGHTS
Helps to illuminate work surface

SPECIFICATIONS

Power	500 MW0
Drum Capacity	3/8" x 35'
Compatible Pipe Sizes	Up to 3" pipes
Included Cable	5/16" x 25'
Light	Up to 70 lumens
Tool Height	11.5"
Tool Length	16.14"
Tool Weight (Tool Only)	11.7 lbs

REPLACEMENT DRUM AND CABLE (sold separately)

TOOL	MODEL #
Drum	DCD2000
Cable	DCD2005

AVAILABLE OPTIONS

DCD200B



20V MAX* Drain Snake, (1) DCD2005
5/16" x 25' (7.93 mm x 7.62 m) Black
Oxide Drain Cable with Bulb Head

DCD200D1



DCD200 20V MAX* Drain Snake, (1) DCD2005
5/16" x 25' (7.93 mm x 7.62 m) Black Oxide
Drain Cable with Bulb Head, (1) DCB203 XR®
Lithium Ion Battery (2.0 Ah), Charger and Kit box.

ACCEPTS 3/8" CABLE UP TO 35FT.

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

DEWALT

DCS350 20V MAX* THREADED ROD CUTTER

20V^{MAX}
LITHIUM ION

CUTTING CAPACITY

Cut most common sizes of threaded rod

MILD STEEL: 1/4", 3/8", 1/2"
STAINLESS STEEL: 1/4", 3/8"

INCLUDED CUTTING DIE

4-Sided, rotatable die allows you to cut 3 sizes of rod with the same set of dies

BRIGHT LED LIGHT
Helps illuminate cutting area

ERGONOMIC HANDLE AND GRIP

Designed to make it convenient for overhead cutting

**PERFORM
PROTECT**

SAVES TIME WITH NO NEED TO CHASE OR FILE DOWN THREADS
No flakes or dust created from fast moving blades or wheels

SPECIFICATIONS

Voltage	20V MAX*
Strokes/Min	30 spm
Tool Weight (Tool Only)	8.8 lbs
Cuts/Charge	350 on 3/8" threaded rod (using DCB2113 battery)

REPLACEMENT CUTTING DIES (sold separately)

SIZE	MODEL #
3/8"	DCS35038
1/2"	DCS35012
1/4", 3/8", 1/2"	DCS3501

AVAILABLE OPTIONS

DCS350B 20V MAX* Threaded Rod Cutter (Tool only)



DCS350D1 20V MAX* Threaded Rod Cutter Kit



(1) DCS350 Threaded Rod Cutter, (1) DCB203 20V MAX* Lithium Ion Battery (2.0Ah), 12V/20V MAX* Charger, (2) 4-Sided Cutting Dies, Die Adjustment Wrench, Kit Bag

CUT THREADED ROD WITH NO CHIPS, SPARKS OR BURRS

DeWALT's Perform & Protect™ line of tools is designed to provide a high level of one or more of the following: control, dust containment or low vibration, without sacrificing performance.

PART OF

20V MAX*
LITHIUM ION

GET MORE DONE.

with our 20V MAX* System. All tools come with upgraded features, superior ergonomics and use Lithium-Ion batteries. For extreme performance, step up to the XR® series and get advanced electronics, extended runtime and faster application speeds.



100+
PRODUCTS

OUR
FASTEST GROWING
SYSTEM

FOR INFORMATION ON ALL 20V MAX* LITHIUM ION TOOLS VISIT
WWW.DEWALT.COM

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

† DEWALT 20V MAX* vs. DEWALT 18V NiCad.

DEWALT

DCE200 20V MAX* PIPE PRESSING TOOL

20V^{MAX*}
LITHIUM ION

1/2"- 4"

CRIMPING CAPACITY

Completes full range of presses & compatible with leading manufacturers pressing jaws, rings, and attachments

BLACK GALVANIZED COATING

For corrosion protection

320°

PIVOTING HEAD

To maneuver in tight spaces

FORWARD/REVERSE

Easy and convenient one handed operation

BRIGHT LED

Helps to illuminate

RUBBER OVERMOLD GRIP

Comfortable & ergonomic

SHOULDER STRAP RING

Attachment point for shoulder strap

BRIGHT LED INTERFACE

On/off, battery level, cycle completed, recalibration & service indication



SPECIFICATIONS

Voltage	20V MAX*
Capacity	1/2" - 4" Copper/Steel 1/2" - 2" FEX/Carbon Steel
Tool Weight (tool only)	7.8 lbs (3.56 kg)

AVAILABLE OPTIONS

DCE200M2



20V MAX* Pipe Pressing Tool, (2) DCB204
20V MAX* XR* Premium Lithium Ion
Batteries (4 Ah), Charger, Shoulder Strap,
Micro USB Cable, Kit Box

DCE200M2K



20V MAX* Pipe Pressing Tool, (2) DCB204
20V MAX* XR* Premium Lithium Ion Batteries (4 Ah),
(6) Jaws, Charger, Shoulder Strap, Micro USB
Cable and Kit Box

**REAL TIME DIAGNOSTICS.
BETTER PERFORMANCE.**

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.



CRIMP. TRACK. REPORT.™

INSTANT ON BOARD DIAGNOSTICS

On board diagnostics show tool performance on the job.

- Power On/Off
- See battery state of charge
- Know when cycle was successful
- Alerts when service or calibration is needed
- Notifies when outside of operating temperature range



GET DETAILED REPORTS WHEN THE JOB IS DONE.

Crimp Connect™ Intelligence is integrated in our Crimping Tools. Download the software at www.DEWALT.com/PLUMBING and hook your tool up using the included USB.



- Date, time and force of press
- Calibration dates
- Number of presses on tool, presses since last calibrated, and remaining presses until next calibration
- Customize report with jobsite and user information
- Ideal for jobsite inspections

ACCESS THE SOFTWARE AT
WWW.DEWALT.COM/PLUMBING

DEWALT®

MECHANICAL

PLUMBING



TOOLS

GUARANTEED TOUGH™

3
YEAR

LIMITED
WARRANTY

1
YEAR

FREE
SERVICE

90
DAY

SATISFACTION
GUARANTEE

DCB204 BATTERY

GUARANTEED TOUGH™

3
YEAR

LIMITED
WARRANTY

3
YEAR

FREE
SERVICE

DCB203 BATTERY

GUARANTEED TOUGH™

3
YEAR

LIMITED
WARRANTY

2
YEAR

FREE
SERVICE

Dealer Stamp.

1-800-4-DEWALT

www.DEWALT.com

Copyright ©2017 DeWALT. The following are examples of trademarks for one or more DeWALT power tools, accessories, anchors, and concrete adhesives: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the MT box configuration; and the array of lozenge-shaped humps on the surface of the tool.

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.

† DEWALT 20V MAX™ vs. DEWALT 18V MAX.