

# DEWALT®



**WIDE SOLID STEEL HANDLE**

Features a rounded I-Beam design for comfort and control

**PRECISION JAWS**

Engineered to facilitate minimal jaw movement between moveable and fixed jaws for precise adjustments

**EXTRA WIDE JAW CAPACITY**

For a larger range of fasteners

**FLARED END ON HANDLE**

Helps prevent hand slipping off during use

**LASER ETCHED MARKINGS**

For precise adjustments

**EXTENDED LENGTH JAWS**

For added reach into tight spaces

**LIFETIME WARRANTY**  
**GUARANTEED TOUGH.™**

**THE ADVANTAGE**

**EXTRA WIDE JAW CAPACITY FOR A LARGER RANGE OF FASTENERS**

**ALL-STEEL ADJUSTABLE WRENCHES**

**DWHT80268**  
(PICTURED)



› These new adjustable wrenches also feature industry leading wide jaw widths.



› The oil rubbed coating will help prevent rust and jobsite wear over time.

## SPECIFICATIONS

SKU	DWHT80092	DWHT80266	DWHT80267	DWHT80268	DWHT80269	DWHT80270	DWHT80273	DWHT80274	DWHT80272
<b>Nominal Size</b>	4in / 100mm	6in / 150mm	8in / 200mm	10in / 250mm	12in / 300mm	15in / 375mm	18in / 450mm	24in / 600mm	Spud
<b>Overall Length</b>	4.37in / 111mm	6.14in / 156mm	8.11in / 206mm	10.31in / 262mm	12.24in / 311mm	14.84in / 377mm	18.27in / 464mm	23.58in / 599mm	16.14in / 410mm
<b>Head Width</b>	1.81in / 46mm	2.09in / 53mm	2.44in / 62mm	3.07in / 78mm	3.62in / 92mm	4.21in / 107mm	5.35in / 136mm	5.67in / 144in	3.62in / 92mm
<b>Jaw Depth</b>	0.75in / 19mm	0.94in / 24mm	1.14in / 29mm	1.34in / 34mm	1.49in / 37.8mm	1.77in / 45mm	2.17in / 55mm	2.17in / 55mm	1.49in / 37.8mm
<b>Jaw Tip Thickness</b>	0.20in / 5.1mm	0.15in / 3.9mm	0.22in / 5.7mm	0.35in / 9mm	0.43in / 10.8mm	0.57in / 14.6mm	0.59in / 14.9mm	0.59in / 14.9mm	0.43in / 10.8mm
<b>Head Thickness</b>	0.43in / 11mm	0.43in / 11mm	0.51in / 13mm	0.63in / 16mm	0.71in / 18mm	0.83in / 21mm	1.08in / 27.5mm	1.10in / 28mm	0.71in / 18mm
<b>Max Handle Thickness</b>	0.22in / 5.5mm	0.24in / 6mm	0.31in / 8mm	0.31in / 8mm	0.47in / 12mm	0.59in / 15mm	0.63in / 16mm	0.63in / 16mm	1.06in / 27mm
<b>Full Jaw Opening</b>	5/7in / 18mm	1-1/32in / 26mm	1-20/77in / 32mm	1-13/32in / 35mm	1-17/26in / 42mm	2-2/35in / 52.25mm	2-19/67in / 58mm	2-23/33in / 68.5mm	1-17/26in / 42mm
<b>Proof Torque - LBF (in)</b>	780	1,885	2,700	5,850	7,650	19,500	19,500	32,500	9,945
<b>Proof Torque - N (mm)</b>	88,129	212,971	305,059	660,961	864,334	2,203,204	2,203,204	3,462,007	1,123,634



The new DEWALT® line of adjustable wrenches features a refreshed look and a design that includes a lighter more balanced weight (in comparison to DEWALT's first line of adjustable wrenches) and comfortable handle to help reduce fatigue over a period of use. Offered in 9 sizes ranging from 4" to 24" and including a spud construction wrench, the DEWALT® adjustable wrench line has the right tool size available for most jobs at hand.

Dealer Stamp

**1-800-4-DEWALT**

**www.DEWALT.com**