DEWALT®

COMPLETELY COMPLESS







CUICKUGSS 3/8" to 5/8" hardwood floo engineered Both solid or

FLOORING **DNIJJATSNI**





*XAM V0S



MIRT ROIRSTX3 FLOORING INSTALL **GOOWGRAH** CASING BASEBOARDS

своми могріме



*XAM V0S

PANELING EURNITURE CABINETRY





ЗНОЕ МОГДІИС MOLDINGS

20V MAX*

KIL INCTNDES

MOLDINGS **DECORATIVE**











(mm 6.63 - 8.81) "8\f-S - "8\d **BBAD NAILER / DCN680**



20% SHUSHESS

.8F



1/2" - 1-1/2" (12.7 - 38.1 mm) **EFOOBING STAPLER / DCN682**

STRENGTHS

AND WE'RE EXPANDING OUR LINE

TO GET YOU RIGHT TO WORK

FROM **START**

1-1/4" – 2-1/2" (32-64 mm) **PNGLED FINISH NAILER / DCN650**

SOM SHIPPINGS STATES

DEWALT





FASTEST GROWING



Copyright ©2017 DEWALT. The following are trademarks for one or more DEWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the "D"-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

DEWALT

1/2" – 1-1/2" (12.7 mm - 38.1 mm)

NARROW CROWN STAPLER / DCN681

CORDLESS CONFIDENCE

BUILDINGON

OUR 20V MAX* NAILERS CHANGED THE GAME.



TACKLE JOBS BOTH LARGE AND SMALL WITH THE FEATURES OF A PNEUMATIC TOOL AND THE FREEDOM OF CORDLESS.

WITH

CORDLESS

CONFIDENCE

DWCDLSNLRBR

*Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18.